

**ENERGY CONSERVATION STRATEGIES IN THE CONTEMPORARY  
SRI LANKAN HIGH-RISE BUILDINGS WITH SPECIAL REFERENCE  
TO FORM AND ORIENTATION**

1. Vague - enclosure?  
geometry?  
Plan form?  
Sectional form?

**The Dissertation Presented to the Faculty of Architecture**

**Of the University of Moratuwa for the**

**Final Examination in M.Sc (Arch.)**



Electronic Theses & Dissertations  
www.lib.mrt.ac.lk

LIBRARY

UNIVERSITY OF MORATUWA, SRI LANKA  
MORATUWA


Master of Science (Architecture)

72 "04"

72 (043)

**U. Kosala Perumpuli Arahchi**

**January 2004**



University of Moratuwa



85460

85460

85460

### **DECLARATION**

I declare that this dissertation represents my own work, except where due acknowledgement is made, and that it has not been previously included in a thesis, dissertation or report submitted to this university or to any other institution for a degree, diploma or other qualification.

.....U.K.P. Arachchi.....

(U.K.Perumpuli Arachchi)

# Abstract

This study is focused on the Energy Conservation Strategies of the contemporary high-rise buildings in Sri Lanka with special reference to the building form and the orientation.

In the future energy becomes a more important factor because there are limited resources, which can be used to generate energy. The huge component of the generated energy used by the commercial buildings (30%) and they have to pay huge sum of money for that. Therefore it's important to study the energy conservation methods, which can be used in every stages of built environment.

In this study selected current multi-storey office buildings, which are located in urban context (Colombo) and from that identified average requirements for 'typical multi storey building' space including equipments and occupants. That 'typical space' and requirements arranged into five different forms of models (computer generated) and tested them for different orientations.

From the cooling load calculate the energy requirement in different stages and from that identified the most (suitable) conditions for Sri Lankan urban context. In conclusion recommendations have been made for a better and suitable Architectural Form of high-rise building and suitable Orientation for Sri Lankan urban context.

what is existing  
↓  
what is not known  
↓  
what you did  
↓  
what you found

→ what is the most suitable condition  
what is the recommendation

# Acknowledgement

---

It is with grate appreciation that I wish to thank in all sincerity all those who gave me valuable advice and various forms of assistance that contributed towards the success of this dissertation. I remember them with gratitude.

Dr. Rohinton Emmanuel, Senior lecturer and supervisory tutor, who have been supported of the whole process and for the valuable comments, suggestions and constructive guidance kindly rendered by him all through.

Arch. Presanna Kulatilaka, Co-ordinator who have been support for structuring the process and for the valuable criticism and encouragement at the initial stage.

Arch. Gamini weerasinghe, Arch. Rohithan Ratnam, helping to get access to buildings and providing all necessary information and details for the study.

Narein, Aruna and Gamini for providing necessary assistance and information at the time of need.

Finally to dear mother, father and brother for their persistent support right throughout.

# Contents

---

**Abstract**

**Acknowledgement**

**List of illustration** VII

**Introduction** 1

Topic Explanation

Architectural Problem/ issue

Justification

Objectives

Limitations

Method of study

## **Chapter one – Energy Efficiency as a key Attribute in the Architecture of High-rise Buildings**

1.1	An Architectural definition of a skyscraper	5
1.2	Factors that determine energy efficiency in High-rises	7
1.2.1	Physical context	7
1.2.1.1	Sun path	7
1.2.1.2	Urban Heat Island	9
1.2.2	Form	11
1.2.3	Orientation	11
1.2.4	Materials of the building	12
1.2.4.1	Wall materials	12
1.2.4.2	Interior & Exterior colour	14
1.2.4.3	Window glass type	15
1.2.4.4	Shading devices	19
1.3	Patterns of Energy Consumption in Buildings	20
1.3.1	Embodied Energy	20
1.3.2	Operational Energy	21
1.4	Energy Consumption patterns in Sri Lankan High-rise Buildings	21
1.5	Energy Conservation patterns in Traditional Sri Lankan Buildings	24
1.5.1	Site Planning	24
1.5.2	Material Selection	24

1.5.3	Use of Natural Lighting & Ventilation	25
1.5.4	Design for Flexibility	26
1.5.5	Climatic Response	27
1.6	Natural Light as an Energy Conservation Attribute in buildings	27
1.6.1	Day light as a Energy	29
1.6.2	The sky as a light source	30
1.7	Architectural form of a high-rise as an energy conservation attribute	31
1.7.1	Factors, which determine the form of a high-rise	31
1.7.2	Effects of cooling load no the form of building	32
1.8	Orientation of the high-rises as an energy conservation attribute	33
1.8.1	Factors, which determine the Orientation of building	35
1.8.2	Effects of cooling load no the Orientation of building	35
1.9	Concluding Remarks	37

## **Chapter 02- Thermal Comfort and Built Environment in Sri Lanka**

2.1	Man & The Thermal comfort	38
2.1.1	Thermal comfort	38
2.1.2	Factors effecting for thermal comfort	39
2.1.3	Environmental Variables Affecting Thermal Comfort	39
2.1.4	Human body Temperature Regulations	40
2.2	Thermal comfort and Comfort Zone of the Building	41
2.2.1	Standard Methods of Developing Comfort Zone	42
2.2.2	Thermal Comfort in Sri Lankan High-rises	43

## **Chapter 03 - Computer Simulation in Architecture**

3.1	Importance of Computer Simulation in Early Design Stage	44
3.2	Computer Simulation	46
3.2.1	Principle Of Simulation	46
3.2.2	The Uses Of Simulation	46
3.2.3	Building Model Creation	47
3.3	Pre Design Computer Analysis Tools In The World	47
3.3.1	DOE – 2	47
3.3.2	ESP-r	49
3.3.3	ENERGY –10	50



3.4	DEROB – LTH	53
3.4.1	General Introduction	53
3.4.2	The Output results obtainable from DEROB	56
3.4.2.1	Limitations and General Assumptions	56
3.4.3	Text Data Produced by DEROB	58
3.4.3.1	Calculated Result in File Vol- load	58
3.4.3.2	Calculated Result in File Surf – tmp	58
<b>Chapter Four – Methodology</b>		
4.1	Development of the ‘typical high-rise building’	59
4.1.1	Input Data	62
4.1.1.1	Climatic Data	62
4.1.1.2	Internal Loads	62
4.1.2	Analysis Technique	64
4.2	Case Studies	
4.2.1	Case Study – 1	65
4.2.2	Case Study – 2	70
4.2.3	Case Study – 3	75
4.2.4	Case Study – 4	80
4.2.5	Case Study – 5	83
<b>Chapter Five – Result and Discussions</b>		
5.1	Orientation as an energy conservation strategy	87
5.1	Form of a building as an energy conservation strategy	93
<b>Conclusion</b>		96
Summary of Findings		
Recommendations		
Limitations of Study		
Directions for further study		
<b>Appendix-A</b>		99
<b>Bibliography</b>		100

# List of illustrations

---

## Chapter 1

Fig. 1.1 San Gimignano towers	5
Fig. 1.2 Flying buttresses: Notre Dame Cathedral	5
Fig. 1.3 First steel skyscraper: Home Insurance Building	6
Fig. 1.4 Minneapolis skyline	6
Fig. 1.5 Petronas Towers - Malaysia	6
Fig. 1.6 World Trade Centre at U.S.A	6
Fig. 1.7 Sun rise	7
Fig. 1.8 The Sun in the sky during the Spring and Fall Equinox in the Northern hemisphere.	8
Fig. 1.9 The Sun in the sky during the summer in the Northern hemisphere	8
Fig. 1.10 The Sun in the sky at different times of the year in the Northern hemisphere	9
Fig. 1.11 Sketch of an Urban heat island profile	10
Fig. 1.12 Different forms of the buildings	11
Fig. 1.13 Building in different orientations	12
Fig. 1.14 Illustrating unit conductivity	14
Fig. 1.15 Heat Absorption percentage of light & dark colours	14
Fig. 1.16 Solar radiation transmission through 6mm clear glass	16
Fig. 1.17 Glass arrangement which reduce entering solar radiation (heat)	17
Fig. 1.18 Unit which help to reduces the outside heat entering inside	18
Fig. 1.19 Energy Consumption of major sectors	22
Fig. 1.20 Energy Consume Patterns in High-rise Buildings	23
Fig. 1.21 Lighting arrangement of a cave temple	26
Fig. 1.22 Different forms of the High-risers	31
Fig. 1.23 The effect of the wind force for two different shapes of buildings	31
Fig. 1.24 Effect of the solar radiation on the rectangular shape building	32
Fig. 1.25 Effect of the solar radiation on the square building	32
Fig. 1.26 Shape of the Bank of Ceylon building	32
Fig. 1.27 concept of architectural lighting	34
Fig. 1.28 Effect of the solar radiation on the rectangular shape building (Angle 01)	36
Fig. 1.29 Effect of the solar radiation on the rectangular shape building (Angle 02)	36
Fig. 1.30 Effect of the solar radiation on circular Shape Building	36



## **Chapter 4**

Fig.no 4.1 Bank of Ceylon Building	59
Fig.no. 4.2 World trade centre Building	60
Fig.no. 4.3 Ceylinco Seylan Towers Building	60
Fig.no 4.4 Model # 1	63
Fig no 4.5 Model # 2	63
Fig.no : 4.6 Model # 3	64
Fig.no: 4.7 Model # 4	64
Fig. no: 4.8 Model # 5	64
Fig no.4.9-4.13 Rectangular building 01 - angle 0 temperature distribution graphs	65
Fig no.4.14-4.18 Rectangular building 01 - angle 20 temperature distribution graphs	66
Fig no.4.19-4.23 Rectangular building 01 - angle 45 temperature distribution graphs	67
Fig no.4.24-4.28 Rectangular building 01 - angle 70 temperature distribution graphs	68
Fig no.4.29-4.33 Rectangular building 01 - angle 90 temperature distribution graphs	69
Fig no.4.34-4.39 Rectangular building 02 - angle 0 temperature distribution graphs	70
Fig no.4.40-4.45 Rectangular building 02 - angle 20 temperature distribution graphs	71
Fig no.4.46-4.51 Rectangular building 02 - angle 45 temperature distribution graphs	72
Fig no.4.52-4.57 Rectangular building 02 - angle 70 temperature distribution graphs	73
Fig no.4.58-4.63 Rectangular building 02 - angle 90 temperature distribution graphs	74
Fig no.4.64-4.69 Square building - angle 0 temperature distribution graphs	75
Fig no.4.70-4.75 Square building - angle 20 temperature distribution graphs	76
Fig no.4.76-4.81 Square building - angle 45 temperature distribution graphs	77
Fig no.4.82-4.87 Square building - angle 70 temperature distribution graphs	78
Fig no.4.88-4.93 Square building - angle 90 temperature distribution graphs	79
Fig no.4.94-4.103 Odd form building 01-angle 0 & 20 temperature distribution graphs	80
Fig no.4.104-4.113 Odd form building 01- angle 45 & 70 temperature distribution graphs	81
Fig no.4.114-4.123 Odd form building 01-angle 90 & 180 temperature distribution graphs	82
Fig no.4.124-4.133 Odd form building 02-angle 0 & 20 temperature distribution graphs	83
Fig no.4.134-4.143 Odd form building 02- angle 45 & 70 temperature distribution graphs	84
Fig no.4.144-4.153 Odd form building 02-angle 90 & 120 temperature distribution graphs	85
Fig no.4.154-4.163 Odd form building 02-angle 90 & 120 temperature distribution graphs	86

## Chapter 5

Fig. no. 5.1 Hourly cooling load values of rectangular building form 01	87
Fig. no. 5.2 Total cooling load values of the rectangular form building 01 at different orientations	88
Fig. no. 5.3 Hourly cooling load values of rectangular building form 02	88
Fig. no. 5.4 Total cooling load values of the rectangular form building 02 at different orientations	89
Fig. no. 5.5 Hourly cooling load values of Square building form	89
Fig. no. 5.6 Total cooling load values of the square form building at different orientations	90
Fig. no. 5.7 Hourly cooling load values of the odd form building	90
Fig. no. 5.8 Total cooling load values of the Odd form building 01 at different orientations	91
Fig. no. 5.9 Hourly cooling load values of the odd form building 02	91
Fig. no. 5.9 Total cooling load values of the Odd form building 02 at different orientations	92
Fig.no 5.10 Summary of the cooling loads at 0 angle	93
Fig.no 5.11 Summary of the cooling loads at 20 angle	93
Fig.no 5.12 Summary of the cooling loads at 45 angle	94
Fig.no 5.13 Summary of the cooling loads at 70 angle	94
Fig.no 5.14 Summary of the cooling loads at 90 angle	95

# Introduction

---

## Topic Explanation

Changes in energy supply and energy source have the most profound effect on building design and urban form since the beginning of the industrial revolution. During most of the last century, architects and engineers have designed buildings free of the natural constraints out of which all-great architectural springs. Chances are that buildings now on designing stage or in construction stage will still be standings at least in the next fifty years from now on and therefore it should be suitable for the future in every ways. *Vague*

When considering about the energy consumption patterns and the amount, large part of the energy is consumed by the commercial buildings of the urban context. Also considerable amount of energy is used by high-rise commercial and office buildings (non domestic buildings) when compared with domestic and public requirements.

The energy consumption of the building is very important because the resources such as hydropower, coal, fuel, nuclear power, gas... etc that can use to produce energy is limited in the world and spread in certain places of the world.

The major problem of this was the poor countries, which haven't fossil fuel or huge capital and facility to produce other energy producers such as nuclear power, should expend large amount of money every year for energy production. It will badly affect the country because they spend the money for energy, which can be used for the development of the country.

In the next two or three decades the high-rise and medium-rise buildings cover considerable range of the urban lands to complete human day to day requirements because the limited land remaining in urban context. Also those buildings need high amount of energy to create and maintain the comfortable microclimate inside them. To arrange good environment inside the building all the components such as temperature, humidity, lighting level... etc have to be controlled artificially because in the present and in the future the outside environment was not at comfortable level.

Architects have great responsibility about the energy consumption of the buildings because architecture is a complex involving of technical, social, utilitarian, cultural and as well as energy conservation of built environment. If the architect didn't consider about the energy consumption patterns of the building the company or the

client who own the building will have to pay large amount of money for energy consumption in every month.

According to the research of California university, they show that new building could be designed to current standards of comfort, use and economy and make full use of the potential of renewable resources such as solar energy, as well as conserving existing fossil fuels. They also design energy efficient office building by discovering that through a careful orchestration of techniques – including reduction of unnecessary lighting levels, careful attention to orientation and the shape of the building and other techniques compatible with the specific microclimate. Finally they found that building consume less than 20% of the energy used by buildings built few years ago.

(Watson,D: 1977)

The below chart percentages show approximate energy consumption of the high-rise buildings in Sri Lanka urban context. (Reference) ??




Fig. 1 Energy Consumption in High-rise Buildings

According to above data 80 % of energy used for air conditioning and artificial lighting requirements of the building. Therefore its more important to study the energy consumption patterns for the artificial lighting and air conditioning the building and what are the possible ways which can reduce the energy consumption for those items. In Sri Lankan climate more than 300 days are sunny days and consequently considerable amount of energy, which use for artificial light can reduce very easily by using the natural light for office activities.

For that its very important to consider the different aspect deeply such as the shape of the building, orientation of the building, wall areas faced to direct sunlight and their external texture, external wall colour and reflectance quality of those wall material, window arrangements the type of glass use for windows and their positions ... etc. at

the early designing stage as well as the construction stages until completion the building.

### **Architectural Problem / Issue**

Today most of the designers/ Architects aren't considering the form of the building and orientation related to the energy consumption of the building. They consider the elevation or the skin of the building only related to create attractive appearance because present day they were not much responsible about the amount of energy consumption by that building when it functions. According to above explanation the energy efficient building becomes one of the most important concepts in the future and the Architects should give grate consideration about that reason. When designing an energy efficient high-rise building without destroy the thermal comfort of the user, appropriate (ideal) standards could be obtained; thereby the study could guide designers to produce energy efficient high-rise building at the same time pay adequate consideration to user comfort.

### **Justification**

In present days the outdoors temperature increases up to very uncomfortable level and as a result most of the commercial and office buildings use air-conditioning systems to create comfortable microclimate in-side the building. Consequently those buildings use high amount of energy for air-conditioning (ventilation) and lighting to maintain their microclimate inside them. The aim of the study is to analyse how the building shape and orientation can use to create energy efficient building without destroying the comfortable microclimate of the high-rise buildings. It is true that the energy consumption for artificial lighting in daytime and air-conditioning is not a big fraction of the total consumption of the country's energy consumption in present day. But in the future this matter can be a huge problem (the energy consumption in high-rise buildings) if we don't considers this today. Also the energy is expensive and awareness of energy saving at each level has become more important in present day as well as in the future. The Architect is no exception and he should do his part towards energy saving. Since there is no doubt that the study of this section is timely and worth studying for the present day and for the future designs.

## Objectives

- Analyse the selected aspects of the orientation and the shape of the high-rises which suitable to Sri Lanka
- Formulate appropriate standards and suggestions for the high-rises, which can apply in the designing stage.
- Guidelines for designers (Architects) to create an energy conscious design (buildings).

## Limitations

- All types of high-rise buildings could not be analysed as a simulation is carried out for hypothetical high-rise building.
- The study is concentrated for only five shapes of high-rise building types.
- The study is concentrated on air-conditioned high-rise buildings only.

The results and discussions are based on DEROB computer program simulations and the limitations of this software are also to be considered.



University of Moratuwa, Sri Lanka.  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)

## Methods of Study

Two different shapes of high-rise buildings (air-conditioned) in Sri Lanka have been identified and analysed their energy consumption pattern. After that creates them as computer-programmed models and analyse their energy consumption when change the orientation remaining same comfortable limitations.

Likewise various shape of high-rise building models simulated by the computer analyse their energy consumption patterns in different orientations. From that identify the most suitable shape and orientation of the high-rise building for Sri Lankan context.